L10	0	(port adj translat$4) with arp	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 19:51
L11	1	(port adj translat$4) same arp	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 19:51
L12	59	(port adj translat$4) and arp	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 20:04
L13	31	local with loop with back with (router gateway)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 20:07
L14	48	((gateway router) with (map$4 translat$4 conver$6) with (mac address) with port with ip).clm.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 20:09
L15	1	((gateway router) with (map$4 translat$4 conver$6) with mac with address with port with ip). clm.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 20:17
L16	2928	destination with (intermediate source) with address with ("same" identical loop$4)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 20:18
L17	26	16 with local with IP	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 20:33
L18	11	17 and arp	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 20:18
L19	16	16 with arp with IP	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2007/07/17 20:33